

# Fomblin Y-LVAC 06/6

AUSIMONT USA, Inc.  
10 Leonards Lane  
Thorofare, NJ 08086  
856-853-8119

## Section 1 - Chemical product and Company information

Date Revised: August 10, 2000  
Product Name: Fomblin Y-LVAC 06/6  
Chemical Name: Propene, 1,1,2,3,3,3-hexafluoro, oxidized, polymerized  
Chemical Family: Fluorocarbons, Perfluorinated polyethers  
Synonyms: None  
Emergency Telephone: 800-424-9300 (CHEMTREC, 24 hours)  
856-853-8119

## Emergency Overview:

Clear, colorless liquid. Thermal decomposition will generate hydrogen fluoride (HF), which is corrosive.

## Section 2 - Compositional information

Name:	CAS#	Approximate Weight (% wt.):
Propene, 1,1,2,3,3,3-hexafluoro, oxidized, polymerized	69991-67-9	100

## Section 3 - Potential Health Effects

### Effects of Overexposure:

Eye Contact  
Eye contact may cause slight irritation.

Skin Contact  
Skin contact may cause slight irritation.

Inhalation  
Inhalation of vapors or mists may cause respiratory tract irritation.

Ingestion

Not an expected exposure route. Ingestion may cause nausea and vomiting.

## **Section 4 - First Aid Measures**

### **Eye Contact:**

Flush eyes for 15 minutes with copious amounts of water, retracting eyelids often. Seek medical attention if irritation persists.

### **Skin Contact:**

Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes.

### **Inhalation:**

If symptoms of irritation, discomfort or overcome by exposure, remove affected person to fresh air. Give oxygen or artificial respiration as needed.

### **Ingestion:**

If conscious, drink three to four 8 ounce glasses of water or milk. Call a physician. If unconscious, immediately take affected person to a hospital. Do not give anything by mouth to an unconscious person.

## **Section 5 - Fire Fighting Measures**

Flash Point: Not Applicable

Lower Explosive Limit: Not Applicable

Upper Explosive Limit: Not Applicable

Autoignition Temperature: Not Applicable

Extinguishing Media: Water (spray or fog), foam, dry chemical or carbon dioxide (CO<sub>2</sub>).

### **Unusual Fire Hazards:**

Fluoropolymers will degrade upon prolonged heating or in a fire, liberating carbonyl fluoride and hydrogen fluoride (HF). This gas is toxic if inhaled or it comes into contact with moist skin. HF has an ACGIH TLV ceiling limit of 3 ppm (2.6 mg/m<sup>3</sup>) and an OSHA PEL TWA of 3 ppm. Carbonyl fluoride has an ACGIH TLV TWA and OSHA PEL TWA of 2 ppm (5 mg/m<sup>3</sup>).

### **Fire Fighting Procedures:**

Use self contained breathing apparatus (SCBA) and skin protection for acid gas exposure. Do not enter fire area without proper protection. Fight fire from a safe distance. If possible, air monitoring should be performed.

## **Section 6 - Accidental Release Measures**

## **Releases:**

In case of a release or spill, absorb material onto vermiculite or similar inert absorbent. Use Perfluorosolv0 PFS1 Solvent to clean any residual material. Place spilled material into covered container for disposal. Dispose of according to applicable local, state and federal regulations.

Extinguish all ignition sources and evacuate the area. Exercise caution; spill area may be slippery.

## **Section 7 - Handling and Storage**

Wash hands after use and before handling food or applying cosmetics. Do not use tobacco products in the immediate area. Keep containers closed. Keep away from heat, sparks and flames. Do not store near combustible materials.

## **Section 8 - Exposure Controls/Personal Protection**

**ACGIH Threshold Limit Value (8hr. time weighted average)**

None established

**OSHA Permissible Exposure Limit Value (8hr. time weighted average)**

None established

### **Engineering Controls:**

#### **Ventilation Requirements:**

Local Exhaust: Vent vapors or mists generated by processing away from operating personnel. Local exhaust ventilation at a rate of 50 feet per minute.

## **Personal Protective Equipment:**

### **Respiratory Protection:**

No occupational exposure standards have been developed for this material. In situations where exposure to vapors or mists is likely, NIOSH/MSHA approved respirators are recommended. Respirator use limitations made by NIOSH/MSHA or the manufacturer must be observed. Respiratory protection programs must be in accordance with 29 CFR 1910.134.

### **Eye Protection:**

Eye/Face Protection: ANSI Z87.1 approved safety glasses with side shields or equivalent.

### **Skin Protection:**

Rubber or latex gloves recommended but not necessary.

## Section 9 - Physical and Chemical Properties

Appearance: Clear liquid

Color: Colorless

Odor: Odorless

Vapor Pressure: Not available

Vapor Density (Air=1): Not available

Boiling Point: Not available

Melting Point: Not available

Specific Gravity: 1.7 - 1.9

Solubility in Water: Insoluble

Molecular Formula:  $\text{CF}_3\text{-(O-CF-CF}_3\text{-CF}_2\text{)}_n\text{-(O-CF}_2\text{)}_m\text{-O-CF}_3$

Molecular Weight: Not available

% Volatile by Volume: 0

## Section 10 - Stability and Reactivity

### Stability:

This material is stable.

### Reactivity:

This material is not reactive.

### Conditions to Avoid:

Heat, sparks, flames, and other ignition sources; avoid heating above 290o C/554o F.

### Materials to Avoid:

Strong or non-aqueous alkali or Lewis acids above 100o C/212o F.

### Hazardous Decomposition Products:

Thermal decomposition of this product will generate hydrogen fluoride (HF), which is corrosive, causing burns on contact with skin and other tissue.

### Incompatibility (Materials to Avoid):

Alkali metals and halogenated compounds.

## Section 11 - Toxicological Information

Rat oral LD50: greater than 25.65 g/kg

Rat intraperitoneal LD50: greater than 25 g/kg

Rat dermal LD50: greater than 2 g/kg  
Rabbit skin irritation: not irritating  
Rabbit eye irritation: not irritating  
Guinea pig sensitization: not a sensitizer

## **Section 12 - Ecotoxicological Information**

No ecotoxicological information is available for this material.

## **Section 13 - Disposal Considerations**

Waste Disposal: Material, as supplied, is not a hazardous waste. Landfill according to current federal, state and local regulations, or incinerate in a high-temperature incinerator designed to burn fluorine-containing materials. Processing, use or contamination may make this information inaccurate or incomplete.

## **Section 14 - Transportation information**

Shipping Class: Not regulated by DOT.

## **Section 15 - Regulatory information**

All components of this product are listed on the Toxic Substances Control Act (TSCA) Section 8(b) Chemical Inventory and the Canadian Environmental Protection Act (CEPA) provisional domestic substances list (DSL). This product is not a "hazardous substance" as defined by OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is not a "controlled product" as defined by the Canadian Workplace Hazardous Materials Information System (WHMIS).

SARA Section 302 Extremely Hazardous Substances: Not listed

SARA 311/312:

Acute: No

Chronic: No

Fire: No

Reactivity: No

Sudden Release of Pressure: No

SARA Section 313 Toxic Chemicals: Not listed

## **Section 16 - Additional Information**

NFPA Ratings (Scale of 0-4):

Health=1

Fire=0

Reactivity=0

Ausimont USA, Inc. Disclaimer: The above information is accurate to the best of our knowledge. However, Ausimont makes no warranty, either expressed or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon.