

1. Substance/Company Identification

PRODUCT NAME: **PLUS 15A**
CHEMICAL NAME: Petroleum Lubricating Oil
CHEMICAL FAMILY: Petroleum Hydrocarbon
COMPANY: Inland Vacuum Industries
35 Howard Ave
Churchville NY 14428
(585) 293-3330
For Chemical Emergency Call Chemtrec 800-424-9300

2. Composition/ Ingredients

CAS NUMBER: 64742-65-0 , Proprietary Additives
PRODUCT COMPONENTS: Severely Hydro treated Paraffinic

Hydrocarbons

3. Hazards Identification

EMERGENCY OVERVIEW: Oil mist, if generated. US OSHA HAZARD COMMUNICATION STANDARD: Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined not to be hazardous. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

Potential Health Effects:

Inhalation: Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. Inhalation of oil mist or vapors at elevated temperature may cause respiratory irritation.

Eye Contact: Expected to be minor eye irritant

Skin Contact: Repeated or prolonged skin contact may cause dermatitis and defatting.

Ingestion: Not expected to be acutely toxic.

Chronic: None known.

HMIS Hazard Ratings:

HEALTH : 1

FLAMMABILITY: 1

REACTIVITY : 0

Key: 4-Severe 3-Serious 2-Moderate 1-Slight 0-Minimal

4. First Aid Measures

INHALATION: Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

SKIN CONTACT: Flush with large amounts of water. Use soap if possible. Remove severely contaminated clothing and wash before reuse. If irritation persists seek medical attention.

INGESTION: If swallowed, DO NOT induce vomiting.

5. Fire Fighting Measures

FLASH POINT: >199 C

METHOD USED: Cleveland Open Cup

Flammable Limits: not established Autoignition Temp: No data available

EXTINGUISHING MEDIA: Water spray, dry chemical, carbon dioxide (CO₂), foam

FIRE FIGHTING INSTRUCTIONS: Avoid breathing smoke and vapor

FIRE FIGHTING EQUIPMENT: Wear self-contained breathing apparatus

and

protective clothing. Use water spray to keep fire-exposed containers cool.

HAZARDOUS COMBUSTION PRODUCTS: Normal combustion forms carbon dioxide and water vapor; incomplete combustion can produce carbon monoxide.

6. Accidental Release Measures	<p>PROCEDURE TO BE FOLLOWED IN EVENT OF RELEASE: Remove sources of ignition. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Take up small spills with absorbent pads. Large spills may be taken up with pump or vacuum.</p>
7. Handling and Storage	<p>GENERAL: Keep container closed. Store in a cool, well ventilated place. Keep away from heat, sparks and flame. Empty containers may contain residues.</p> <p>STORAGE TEMPERATURE: Ambient</p> <p>STORAGE PRESSURE: Atmospheric</p>
8. Exposure Controls/Personal Protection	<p>EXPOSURE LIMITS: Oil mist if generated: TLV (ACGIH) 5mg/m³-8hr TWA, STEL (ACGIH) 10mg/m³, PEL (OSHA) 5 mg/m³-8hr TWA</p> <p>VENTILATION: Good ventilation at source of vapor</p> <p>PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves and chemical resistant gloves.</p>
9. Physical & Chemical Properties	<p>PHYSICAL STATE: Liquid</p> <p>VAPOR PRESSURE: < 0.01 Torr @ 25C</p> <p>BOILING POINT: 112 C</p> <p>EVAPORATION RATE (n-Bu Acetate = 1): Nil</p> <p>VAPOR DENSITY: approximately 14</p> <p>VOC: NA</p> <p>SPECIFIC GRAVITY: 0.85</p> <p>VISCOSITY: 28 cst @ 40 C</p> <p>SOLUBILITY IN WATER: Nil</p> <p>APPEARANCE: Pale yellow viscous liquid with a faint petroleum odor.</p>
10. Stability & Reactivity	<p>STABILITY: Stable under normal temperatures and pressures</p> <p>CONDITIONS TO AVOID: None known</p> <p>INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents</p> <p>HAZARDOUS POLYMERIZATION: Will not occur</p> <p>HAZARDOUS DECOMPOSITION: None</p>
11. Toxicological Information	<p>Oral Toxicity (rats): Practically non-toxic (LD50: greater than 2000 mg/kg)</p> <p>Dermal Toxicity (rabbits): Practically non-toxic (LD50: greater than 2000 mg/kg)</p> <p>Inhalation Toxicity (rats): Practically non-toxic (LC50: greater than 5 mg/l)</p> <p>Eye Irritation (rabbits): Practically non-irritating. (Draize score: greater than 6 but 15 or less)</p> <p>Skin Irritation (rabbits): Practically non-irritating. (Primary Irritation Index: > than 0.5 but less than 3)</p> <p>Chronic Toxicology: Product not classified as a carcinogen. It contains less than .3% w/w DMSO extract as measured by IP-346.</p> <p>Ecotoxicity: No data available</p> <p>Environmental Fate: This material is not expected to present any environmental problems other than those associated with oil spills.</p>
12. Ecological Information	<p>This product is not regulated by CERCLA/RCRA as a hazardous waste or material. Therefore, it may be disposed of as an industrial waste in a manner acceptable to good waste management practice and in compliance with applicable local, state and federal regulations.</p>
13. Disposal Considerations	<p>Product and packaging must be disposed of in accordance with Federal, State and local regulations.</p>

14. Transport Classification

DOT:

Description Proper Shipping Name: Not regulated
 Hazard class: Not regulated
 ID Number: Not Regulated
 Packing Group: Not regulated
 Special Information: Not Applicable.

IMO:

Proper Shipping Name: Not regulated
 Hazard Class: Not regulated
 Packing Group: Not Applicable
 Special Information: Not applicable
 IMO Label: Not applicable
 Shipping Containers: Not applicable

15. Regulatory Information

TSCA: This material is in compliance with the TOXIC SUBSTANCE CONTROL ACT (15 USC 2601-2629) and is listed in the TSCA Inventory.

HAZARD CATEGORIES FOR SARA 311/312 REPORTING

HEALTH	Immediate (Acute)	No
HEALTH	Delayed (Chronic)	No
PHYSICAL	Fire	No
PHYSICAL	Sudden release of pressure	No
PHYSICAL	Reactive	No
PHYSICAL	Nuisance Mist/ Dust Only	No

01=SARA 313	11=NJRTK	21=TSCA Sect 5(a)(2)
02=MASS RTK	12=CERCLA 302.4	22=TSCA Sect 6
03=NTP Carcinogen	13=MN RTK	23=TSCA Sect 12(b)
04=CA Prop 65-Carcin	14=ACGIM TWA	24=TSCA Sect 8(a)
05=CA Prop 65-ReproTox	15=ACGIH STEL	25=TSCA Sect 8(d)
06=IARC Group 1	16=ACGIH Calc TLV	26=TSCA Sect 4(a)
07=IARC Group 2A	17=OSHA PEL	27=Canadian WHMIS
08=IARC Group 2B	18=DOT Marine Pollutant	28=OSHA CEILING
09=SARA 302/304	20=EPA Carcinogen	
10=PA RTK		

The following components of this material are found on the regulatory lists indicated.

DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

Is found on lists: 14,15,17

NEW JERSEY RTK CLASSIFICATION:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et.seq., the product is to be identified as follows:

PETROLEUM OIL

16. Other Information

The information on this form is furnished solely for the purpose of compliance with the OSHA Act, and shall not be used for any other purpose. The information herein is given in good faith and is based on data considered accurate. However, no warranty, expressed or implied, is made regarding the accuracy of these data or the results to be obtained from the use thereof.